

SPECIFICATIONS

Model		C37EMC
Panel	Screen Size (diagonal)	37"
	Active Display Area (inch mm)	35.421 x 9.962 899.7 x 253.044
	Resolution	1920 x 540
	Aspect Ratio	32 : 9
	Display Colors	16.7M
	Brightness (cd/m ² ; typ.)	700
	Contrast Ratio	4000 : 1
	Response Time (ms; GTG)	8
	Viewing Angle	178° / 178°
	Lifetime (hours)	50,000
	Backlight type	LED
Resolution	Monitor	1920 x 540
Input		1 x HDMI 1 x DVI 1 x VGA(D-Sub) 1x PC Audio
Output		Speaker
Power	Input Voltage	100 – 240V AC
	Power consumption	65 W
Features	PIR Sensor (Motion detection)	No
	Auto Power Control	Yes
	Auto Brightness Sensor	No
Operation	Temperature (°C)	0 - 40
	Humidity (%)	20 - 80
	OSD Language	5 Lang
Dimension	Set Size : W x H x D (inch mm)	36.137 x 11.173 x 1.772 917.92 x 283.85 x 45
	Bezel Size : U/D/L/R (inch mm)	0.567 / 0.567 / 0.319 / 0.319 14.4 / 14.4 / 8.1 / 8.1
	Wall Mounting hole : WxH (mm)	200 x 200 / 500 x 200 (M6)
Weight	Set (lb kg)	20.94 9.5

FEATURES

Special Out-Of-Home LCD Panel

By using commercial grade LCD panels for Out-Of-Home applications, HYUNDAI Digital Signage display can provide higher brightness and contrast than standard LCD TV panels. This guarantees longer working time, deliver clear and bright image contents in the portrait or landscape format without any loss of quality.

Various aspect ratio Utilization

The aspect ratio of 32 : 9 given to you is two times of 16:9 conventional image, it allows to display 2 types of 16:9 contents at once.

24/7 Operation

27/7 operation, thanks to use commercial LCD panels, gives continuous communication to customers.

Captivating design with slim and narrow bezel

DIMENSIONS

[Unit: mm[inch]]

