

SPECIFICATIONS

Model	H325SL	
Panel	Screen Size (diagonal)	32"
	Active Display Area (inch/mm)	27.47 x 15.44 / 697.68 x 392.25
	Resolution	1366 x 768
	Aspect Ratio	16:9
	Display Colors	8 bit~16.7 M
	Brightness (cd/m ² ; typ.)	1500
	Contrast Ratio(typ.)	3000:1
	Response Time (ms; GTG)	8
	Viewing Angle	178° /178° (CR=10)
	Lifetime (hours)	50,000
Backlight type	LED	
Input	VGA (15pin D-Sub)	1
	HDMI	1
	RS-232C	1
	PC audio	1
Output	VGA (15pin D-Sub)	1
	DVI	1
	RS-232C	1
	Speaker	10 W x 2 CH
Power	Operating Voltage	100 – 240V AC
	Consumption (typ.); Normal	145 W
	Consumption (typ.); On Heater	850 W
	Auto Power Control (DPMS)	yes
Features	Auto Cooling System	yes
	Auto Heating System	yes
	Anti-Vandal Glass	yes
	Anti Reflection Coating	yes
	Auto Brightness Sensor	yes
Operation	Temperature (°C)	-20 ~ 45
	Humidity (%)	20 - 80
	OSD Language	10 Lang
Approvals	Ingress Protection	IP65
Dimension	Set (W x H x D), inch/mm	23.23 x 55.53 x 0.45(Base: 23.62) / 590 x 1410.4 x 11.4(Base:600)
Weight	Set (lb/kg)	146.6 / 66.5
Computer		Option

FEATURES

All Weather Capable

Equipped with an intelligent cooling and heating system, HYUNDAI's Outdoor Displays are well suited for withstanding any weather conditions from -20°C to +45°C.

Sunlight Readable Brightness

HYUNDAI provides special displays which are based on the Optical Bonding for installations in environment with the brightest lightning conditions. Make your messages and images clear and readable under even bright sunlight.

Anti-Vandal Protection

Thanks to a special tempered security glass, HYUNDAI's Outdoor Displays are protected against any vandalism attacks using Anti-Vandal glass bonding technique improving in durability from outside damage.

DIMENSIONS

H325SL [unit: mm]

